



CC Rolly




The CC Rolly has the size of half a Europallet and has been developed for conveying modular packaging such as crates, boxes and alcohol packs. The CC Rolly can be used as a display unit in a store. It can also be supplied as a Low Noise Rolly with PIEK certification. For more information see the CC Low Noise Rolly leaflet.

Characteristics and benefits

- Ideal for shop floors.
- The CC Low Noise Rolly can be stacked straight away.
- The frame has smooth rounded corners to ensure that manoeuvring is safer and easier.
- The CC Rolly is built as a load-bearing frame with two fixed and two castor wheels.
- The CC Rolly can be easily moved using pallet trucks, forklift trucks or chain conveyors because of the 4 steel beams that have the same dimensions as the frame.
- Designed to meet the highest hygiene standards.
- Water resistant.

How to hand in?

- Always hand in equipment clean and in a functional state.
- Ensure that the wheels are free from rope, plastic and other waste.
- Ensure that all castor wheels are one one side.
- Ensure there is 1 product type per stack.
- Ensure that the wheels of only 1 colour are present per stack.



Do you have equipment that is broken?


You can then hand it in for repair at a repair shop or exchange it for functional equipment.

Specifications

A = 811 mm
B = 142 mm

C = 182 mm
D = 605 mm


E = 40 mm



Average weight



400 kg UDL*




Accessibility
(4 sided)



Logo recognition



Available
as low noise



Temperature

* UDL = Uniform Distributed Load